

SDN-C Compact DIN Rail Series

The SDN-C DIN rail power supplies are the next generation of the popular SDN series. These models combine high efficiency and compact size with new visual diagnostic LEDs to offer the most performance available from SolaHD. Essential industrial features such as Sag Immunity, Power Factor Correction, and universal voltage input have been retained in this series. Wide temperature operating range and parallel operation capability make the new SDN-C units suitable to a variety of industrial applications.

Features

- Compact packaging to save space on the DIN rail
- New visual diagnostic LEDs for input and output status at a glance
- High MTBF means high reliability and long life
- Higher efficiency saves energy and lowers amount of heat generated in panel
- PowerBoost™ overload capability to start high inrush loads
- Accepts Universal voltage 85-264 Vac, 50/60 Hz input
- Single phase models meet SEMI F47 Sag Immunity standard
- Power Factor Correction (meets EN61000-3-2)
- Class I, Div. 2 Hazardous Locations
 - ATEX approval (pending)
- Patented DIN rail mounting clip
- User Adjustable output voltage accessible via front face
- Parallel capability standard
- Industrial grade design
 - -25°C to 60°C operation without derating
 - Rugged metal case and DIN connector
- User-friendly
 - LEDs for status
 - Large, rugged, accessible screw terminals
 - Easy on/off DIN mounting
- Fully tested and burned-in at factory
- RoHS compliant



UL US
UL 508 Listed
IND. CONT. EQ.
E61379

UL US
UL 60950
E137632
CUL/CSA-C22.2
No. 234-M90

CE
EMC and
Low Volt.
Directive


Related Products

- SDN-P series
- SDP™ series
- SFL series
- SCP series
- SDU UPS

Applications

- Industrial Machine Control
- Process Control
- Conveying Equipment
- Material Handling
- Vending Machines
- Packaging Equipment
- Amusement Park Equipment
- Semiconductor Fabrication Equipment

The SolaHD Difference



LED Light Status Conditions

	Normal	AC Power Loss	AC Input Low	No DC	High Load	Overload	Hot	Too Hot
Input	Green	-	Yellow	Green	Green	Green	Green	Green
Output	Green	-	Green	-	Yellow	Yellow	Green	-
Alarm	-	-	-	Red	Yellow	Red	Yellow	Yellow

Visit our website at www.solahd.com or contact Technical Services at (800) 377-4384 with any questions.


SDN-C Specifications (Single Phase)

Description	Catalog Number		
	SDN 5-24-100C	SDN 10-24-100C	SDN 20-24-100C
Input			
Nominal Voltage	115/230 Vac		
-AC Range	85 - 264 Vac		
-DC Range ¹	90 - 375 Vdc		
-Frequency	43-67 Hz		
Nominal Current ²	1.65 - 0.55 A	3.2 - 1.0 A	6A / 3A
-Inrush current max.	Typ. < 15 A	Typ.< 30 A	< 40 A
Efficiency (Losses ³)	> 90% typ. (12 W)	> 90% typ. (24 W)	> 92% (38 W)
Power Factor Correction	Active power factor correction to better than 0.92		
Output			
Nominal Voltage	24 V (23.5~28.5 Vdc Adj.)		
-Tolerance	< ±2 % overall (combination Line, load, time and temperature related changes)		
Initial Voltage Setting	24.5V ± 1%		
-Ripple ⁴	< 50 mVpp		<100mVpp
PARC	PARC (Periodic and Random Deviation) = 100 mV peak-peak max		
Overvoltage Protection	> 30.5 but < 33 Vdc, auto recovery		
Power Back Immunity	< 35V		
Nominal Current	5 A (120 W)	10 A (240 W)	20 A (480W)
-Peak Current ⁵	1.5 x Nominal Current for 2 seconds minimum while holding voltage > 20 Vdc		
-Short Circuit Current	1.5 x Nominal Current at near zero volts at short circuit condition		
-Current Limit	PowerBoost™		
Parallel Operation	Switch selectable single unit or parallel unit operation. Units will not be damaged by parallel operation (regardless of switch position setting).		
Holdup Time	>20 ms (Full load, 100 Vac Input @ T _{amb} = +25°C) to 95% output voltage		
Voltage Fall Time	<150 mS from 95% to 10% rated voltage @ full load (T _{amb} = +25°C)		
Line and Load Regulation	< 0.5%		
General			
EMC: -Emissions	EN61000-6-2:2001, EN61000-6-3:2001, Class B EN55011, EN55022 Radiated and Conducted including Annex. A, EN61000-3-2		
-Immunity	EN61000-6-1:2001, EN61000-6-2:2001, EN61000-4-2 Level 4, EN61000-4-3 Level 3, EN61000-4-6 Level 3, EN61000-4-4 Level 4 input and level 3 output. EN61000-4-5 Isolation class 4, EN61000-4-11, IEC 61000-4-34 voltage dip immunity standard		
Approvals	UL508 Listed, cULus; UL 60950-1, cURus; IEC60950-1; Class I, Div. 2, Hazardous location approval; CE (LVD 73/23 & 2004/108/EC), (EMC 89/336 & 93/68/EEC); EN61000-3-2		
Temperature ⁷	Storage: -40°C to + 85°C, Operation -25°C to +60°C full power, with linear derating to half power from 60 to 70°C (Convection cooling, no forced air required). Operation up to 50% load permissible with sideways or front side up mounting orientation.		
MTBF ⁶	> 550,000 hrs		> 450,000 hrs
Warranty	5 Years		
General Protection/Safety	Protected against continuous short -circuit, continuous overload, continuous open circuit. Protection Class 1 (IEC536), degree of protection IP20 (IEC60529) Safe low voltage: SELV (acc. IEC60950-1)		
Status Indicators	Visual: 3 status LEDs (Input, Output, Alarm) Relay: N.O. contact rated 200ma/50 Vdc		
Installation			
Fusing -Input	Internally fused		
-Output	Outputs are capable of providing high currents for short periods of time for inductive load startup or switching. Fusing may be required for wire/loads if 2x Nominal O/P current rating cannot be tolerated. Continuous current overload allows for reliable fuse tripping.		
Mounting	Simple snap-on to DIN TS35/7.5 or TS35/15 rail system.		
Connections	Input: Screw terminals, connector size range: 16-10 AWG (1.5-6 mm ²) for solid conductors. Output: Two terminals per output, connector size range: 16-10 AWG (1.5-6 mm ²) for solid conductors.		
Case	Fully enclosed metal housing with fine ventilation grid to keep out small parts.		
-Free Space	15 mm in front, 25 ~ 40 mm above and below, 10 mm left and right.		
H x W x D (inches/mm)	4.88 x 1.97 x 4.55 (124 x 50 x 116)	4.88 x 2.36 x 4.55 (124 x 60 x 116)	4.88 x 3.42 x 4.98 (124 x 87 x 126.6)
Weight (lbs/kg)	1.65 (0.75)	1.98 (0.9)	2.6 (1.2)

1. Not UL listed for DC input.
 2. Input current ratings are conservatively specified with low input, worst case efficiency and power factor.
 3. Losses are heat dissipation in watts at full load, nominal input line.

4. Ripple/noise is stated as typical values when measured with a 20 MHz, bandwidth scope and 50 Ohm resistor.
 5. Peak current is calculated at 24 Volt levels.
 6. Demonstrated through extended life test.
 7. Contact tech support for operation at -25°C.

SDN-C Series Dimensions



Catalog Number	Dimensions – inches (mm)		
	H	W	D
SDN 5–24–100C	4.88 (124)	1.97 (50)	4.55 (116)
SDN 10–24–100C	4.88 (124)	2.36 (60)	4.55 (116)
SDN 20–24–100C	4.88 (124)	3.42 (87)	4.98 (126.6)


SDN-C Series Mounting

DIN Rail Mounting


Snap on the DIN Rail:

1. Tilt unit slightly backwards
2. Put it onto the DIN Rail
3. Push downwards until stopped
4. Push at the lower front edge to lock
5. Shake the unit slightly to ensure that the retainer has locked

Alternative Panel Mount: Using the optional SDN–PMBRK2 accessory, the unit can be screw mounted to a panel.



Detachment from DIN Rail:



SDN-C Series Mounting (cont.)

Chassis Mounting

Instead of snapping a Sola SDN™ unit on the DIN Rail, you can also attach it using the screw mounting set SDN-PMBRK2.

This set consists of two metal brackets, which replace the existing two aluminum profiles.

Dimensions

